

695.1/6

RESERVE COPY
PATENT SPECIFICATION



Application Date : May 21, 1931. No. 14,971 / 31.

371,638

Complete Left : Aug. 8, 1931.

Complete Accepted : April 28, 1932.

PROVISIONAL SPECIFICATION.

Improvements in and relating to Toy Building Blocks.

I, WILLIAM MURPHY, of 2, Harcourt Road, Altrincham, County of Chester, a British subject, do hereby declare the nature of this invention to be as follows:—

This invention relates to toy building blocks which are characterized by perforations on every face, and curved toy building blocks which are characterized by perforations on the inner curved face and on the contiguous side faces, and to connecting pegs or dowels by which the said toy building blocks can be connected together in a variety of ways and erected into structures, this invention also relates to an improved method of forming the said toy building blocks.

It is known to form toy building blocks having circular perforations on every face, and curved toy building blocks having perforations on the inner curved face and contiguous side faces, by the method of cutting wood blocks to the required shape and size and subsequently drilling the said perforations on the faces of the said blocks.

Producing toy building blocks in the said manner is comparatively expensive by reason of the number of machines and skilled operations required for cutting the said blocks to the required shape and size and drilling the perforations on the faces of the said blocks.

One object of this invention is to provide a cheaper method of manufacturing toy building blocks of rectangular, cubical, cylindrical, or prism shape and which are perforated on every face, and curved toy building blocks which are perforated on the inner curved face and on the contiguous side faces.

Another object is to provide improved forms of toy building blocks and connecting pegs or dowels by which the said toy building blocks can be connected together and erected into a variety of structures.

In accordance with this invention, toy building blocks are made of papier-mâche or other suitable solidifiable plastic material which will set hard on drying or baking, and are formed to the required shape and size and perforated on the faces of the block by moulding or press-

ing, the said perforations on the faces of the blocks being formed and located during the shaping of the said toy building blocks by moulding or pressing.

In this way the cost of manufacturing toy building blocks which are perforated on every face, is considerably reduced in comparison with the cost of cutting wood blocks to the required shape and size and subsequently drilling the perforations on the faces of the said blocks.

Also, moulding or pressing facilitates the forming of variously shaped perforations on the faces of the said toy building blocks and thus enables the use of variously shaped connecting pegs, such as for example, circular, rectangular, rhomboidal, or triangular shaped connecting pegs.

In accordance with this invention papier-mâche or other suitable solidifiable plastic material is formed into blocks of rectangular, cubical, cylindrical, or prism shape by moulding or pressing, and uniformly shaped or variously shaped perforations are formed and located at regular and definite distances apart on every face of the said blocks during the shaping of the said blocks by moulding or pressing.

Also in accordance with this invention, curved toy building blocks which are perforated on the inner curved face and on the contiguous side faces, are formed by mould or pressing solidifiable plastic material to the said curved shape, the said perforations on the inner curved face and contiguous side faces being formed and located during the shaping of the said curved toy building blocks by moulding or pressing.

Also in accordance with this invention, connecting pegs or dowels are made of a shape and size that will fit the said perforations on the faces of the said blocks so that the said blocks can be connected together by the said connecting pegs and erected into a variety of structures.

The perforations on the faces of a block can be all of uniform shape, or of various shapes and disposed in a variety of ways on the faces of the said block.

The location of the perforations in the

55

60

65

70

75

80

85

90

95

100

105

faces of the blocks is so arranged that any pair of perforations in one block will coincide with a pair of perforations in another block and the said blocks will 5 build up evenly when connected together

by the insertion of connecting pegs into the appropriate perforations on the faces of the said blocks.

Dated this 20th day of May, 1931.

WILLIAM MURPHY.

COMPLETE SPECIFICATION.

Improvements in and relating to Toy Building Blocks.

I, WILLIAM MURPHY, of 2, Harcourt Road, Altrincham, County of Chester, a British subject, do hereby declare the nature of this invention, and in what manner the same is to be performed, to be particularly described and ascertained in and by the following statement:—

This invention relates to toy building blocks which are characterized by perforations on every face, and to curved toy building blocks which are characterized 20 by perforations on the inner curved face and contiguous side faces, and to connecting pegs or dowels by which the said toy building blocks can be connected together in a variety of ways and erected into structures, and this invention also relates to 25 an improved method of forming the said toy building blocks.

It is already known practice to form toy building blocks which are perforated 30 on every face, and curved toy building blocks which are perforated on the inner curved face and contiguous side faces, by the method of cutting wood blocks to the required shape and size and subsequently 35 drilling circular perforations on the faces of the said blocks.

Producing toy building blocks in the said manner is comparatively expensive by reason of the number of machines 40 and skilled operations required for cutting the said blocks to the required shape and size and drilling the said perforations on the faces of the said blocks.

The objects of this invention are to 45 provide a cheaper method of manufacturing toy building blocks of rectangular, or cubical, or cylindrical, or prism shape, which are perforated on every face, and curved toy building 50 blocks of suitable cross-section which are perforated on the inner curved face and contiguous side faces, and to provide improved forms of toy building blocks and connecting pegs or dowels by which 55 the said toy building blocks can be connected together and erected into a variety of structures. In order to accomplish the aforesaid objects, the present invention comprises the provision of a cheaper 60 method of manufacturing toy building blocks which are shaped and perforated on the faces as hereinbefore specified, the

said cheaper method of manufacturing consisting in making the said toy building blocks of any suitable solidifiable plastic material which will set hard on 65 drying or baking, the blocks being formed to the required shape and size and perforated on the faces of the blocks by means of moulding or pressing to 70 shape, and the said suitable solidifiable plastic material may also be such as can be readily coloured if required.

The present invention also comprises the provision of improved forms of toy 75 building blocks and connecting pegs or dowels by which the said toy building blocks can be connected together and erected into a variety of structures.

By means of moulding or pressing suitable solidifiable plastic material to the required shape and size, the cost of manufacturing toy building blocks which are perforated on the faces as hereinbefore specified is considerably reduced in comparison with the cost of cutting wood blocks to the required shape and size and subsequently drilling the perforations on the faces of the said blocks.

Moreover, the method of moulding or pressing to shape facilitates the forming of variously shaped perforations on the faces of the said toy building blocks and thus enables the use of variously shaped connecting pegs, such as for example, connecting pegs of circular, or rectangular, or rhombic, or triangular cross-section, the said perforations on the faces of the toy building blocks being shaped to correspond with the particular cross-sectional shape or shapes of connecting pegs it is intended to use.

There are many materials which are suitable for use as components of the aforesaid suitable solidifiable plastic material, such as for example, papier-mâché, paper pulp, wood pulp, fibrous material, plaster, cement, clay, and the like, the present invention not being limited to the use of the said particular 105 materials which are only mentioned here as examples and it must be clearly understood that the present invention comprises the use of any suitable solidifiable plastic material.

In accordance with this invention, any

suitable solidifiable plastic material is by means of moulding or pressing to shape, formed into blocks of rectangular, or cubical, or cylindrical, or prism shape, 5 and perforated on every face, the perforations being either of uniform shape or of various shapes and formed and located either centrally on every face or at regular and definite distances apart 10 on every face of the said blocks during the moulding or pressing to shape of the said blocks.

Also in accordance with this invention, any suitable solidifiable plastic material 15 is by means of moulding or pressing to shape, formed into curved blocks of suitable cross-section and with each end of the block suitably shaped for connecting to other blocks, and perforated on the 20 inner curved face and on the contiguous side faces, the perforations being either of uniform shape or of various shapes and formed and located on the said inner curved face and contiguous side faces of 25 the curved blocks during the moulding or pressing to shape of the said curved blocks.

The aforesaid perforations on the faces of the blocks are formed to a circular, or rectangular, or rhombic, or triangular, or other convenient shape as 30 may be required, and are located either centrally on the faces, or at regular and definite distances apart on the faces, or 35 centrally and at regular and definite distances apart on the faces of the said blocks, and the perforations can be either of uniform shape or of various shapes on each block; and disposed in a variety of 40 ways on the faces of the said blocks.

Also in accordance with this invention, connecting pegs or dowels of wood, metal, or other suitable material, are made to a 45 shape and size that will fit the perforations on the faces of the aforesaid toy building blocks so that the said toy building blocks can be connected together by the said connecting pegs or dowels and erected into a variety of structures.

The aforesaid rectangular building blocks are made to convenient dimensions, for instance, into cubical blocks or cubes, and double-cubes (or blocks of the same 50 cross-section size as the said cubes and twice the length of one of the said cubes), the dimensions of other units or elements 55 comprised in a set of blocks being either multiples, or sub-multiples, or sub-divisions of the dimensions of the said cubes or double-cubes, so that they will fit together and build up evenly.

The perforations on the faces of the blocks are located either at the centre of 60 each face of a block, or at regular and definite distances apart on each face of 65

a block so that any pair of perforations on a face of a block will coincide with a pair of perforations on a face of another block, and the said blocks will build up evenly when connected together by the insertion of connecting pegs into the appropriate perforations on the faces of the said blocks. A convenient method of 70 locating the perforations on the faces of the blocks, is to divide the face of a cubical block or cube into sixteen equal squares and locate the perforations on the faces of the blocks so that besides being either central or at regular and definite distances apart, the centres of the perforations will coincide with points of intersection of the lines forming the said 75 sixteen equal squares.

On the faces of curved blocks and on the faces of blocks whose dimensions are either multiples, or sub-multiples, or subdivisions of the aforesaid cubes or double-cubes, the perforations are located at the same distance apart and at the same distance from edges of blocks as corresponding perforations on the faces of the aforesaid cubes and double-cubes, so that when different blocks of a set are connected together by the insertion of connecting pegs into the appropriate perforations on the faces of the blocks, they will build up 80 evenly.

Sets of blocks may be composed of blocks having all perforations on the faces, formed to a uniform shape, and connecting pegs or dowels of corresponding shape to fit the said perforations, and sets of blocks may also be composed of blocks having the perforations on the faces, formed to a variety of shapes, and connecting pegs or dowels of various shapes to fit the said variously shaped 85 perforations.

The accompanying drawings show by way of example various forms of toy 90 building blocks and connecting pegs or dowels made in accordance with this invention, also by way of example various structures made with the said toy building blocks and connecting pegs or dowels. 95

Various modifications may be made in the forms of blocks and shapes of perforations and manner of disposition of perforations on faces of blocks, from those 100 shown in the accompanying drawings, without departing from the scope of the present invention, and it must be clearly understood that this invention comprises other forms of blocks and other shapes 105 of perforations and other dispositions of the perforations on the faces of the blocks besides those shown by way of example on the accompanying drawings.

Various forms of toy building blocks 110 and connecting pegs and structures are 115

shown on the accompanying drawings, as follows:—

The Figs. 1 to 12, show cubical blocks or cubes, perforated on every face, the perforations p being of various shapes and arranged in various ways. The shapes of the perforations p on Figs. 1, 2, 5 and 7, are rectangular; on Figs. 3, 9 and 10, rhombic; on Figs. 4 and 6, circular; on Fig. 8, octagonal, and on Figs. 11 and 12, triangular.

Figs. 13, 14 and 15, show double-cubes, perforated on every face.

Fig. 16, a rectangular block half the size of Figs. 13, 14 or 15.

Fig. 17, a rectangular block half the size of Figs. 5 or 6.

20 Fig. 19, a rectangular block half the size of Fig. 16.

Figs. 20 and 21, three sided prisms or

angle blocks.
Figs. 22, 23, 24 and 30, cylindrical
blocks.

Figs. 25, 26, 27, 28 and 29, connecting pegs or dowels of various cross-sectional shapes, shown as follows:—

Fig. 25, circular, Fig. 26, triangular,
30 Fig. 27, rectangular, Fig. 28, rhombic.
Fig. 29 shows an elongated connecting
peg for use as in structures similar to

Fig. 31. Curved block of rectangular cross-section and perforated on the inner curved face A and contiguous side faces B with perforations μ .

Fig. 32. A wheel structure. Fig. 33. A railway engine.

Having now particularly described

45 Having now particularly described and ascertained the nature of my said invention, and in what manner the same is to be performed, I declare that what I claim is:—

1. Rectangular, or cubical, or cylindri-

Redhill: Printed for His Majesty's Stationery Office, by Love & Malcolmson, Ltd.—1902

cal, or prism shaped toy building blocks of suitable solidifiable plastic material perforated on every face by means of moulding or pressing to shape, and curved toy building blocks of suitable solidifiable plastic material having suitably shaped ends and suitably shaped cross-section perforated on the inner curved face and contiguous side faces by means of moulding or pressing to shape, and in combination with the aforesaid toy building blocks, connecting pegs or dowels to fit the perforations on the faces of the aforesaid toy building blocks, substantially as hereinbefore described and shown.

2. Rectangular, or cubical, or cylindrical, or prism shaped toy building blocks of suitable solidifiable plastic material perforated on every face by means of moulding or pressing to shape, and curved toy building blocks of suitable solidifiable plastic material having suitably shaped ends and suitably shaped cross-section perforated on the inner curved face and contiguous side faces by means of moulding or pressing to shape, substantially as hereinbefore described and shown.

3. Rectangular, or cubical, or cylindrical, or prism shaped toy building blocks of suitable solidifiable plastic material perforated on every face by means of moulding or pressing to shape, substantially as hereinbefore described and shown. 80

4. Curved toy building blocks of suitable solidifiable plastic material having suitably shaped ends and suitably shaped cross-section perforated on the inner curved face and contiguous side faces by means of moulding or pressing to shape, substantially as hereinbefore described and shown. 25
90

5. Toy building blocks, substantially as hereinbefore described and shown.

th day of August, 1931.
WILLIAM MURPHY

371,638 COMPLETE SPECIFICATION

SHEET 1




FIG. 1.




FIG. 2.




FIG. 3.




FIG. 4.




FIG. 5.




FIG. 6.




FIG. 7.




FIG. 8.




FIG. 9.




FIG. 10.




FIG. 11.




FIG. 12.




FIG. 13.




FIG. 14.




FIG. 15.



FIG. 16.




FIG. 17.



FIG. 18.



FIG. 19.




FIG. 20.




FIG. 21.




FIG. 22.




FIG. 23.




FIG. 24.



FIG. 25, FIG. 26, FIG. 27, FIG. 28, FIG. 29

FIG. 30.

[This Drawing is a reproduction of the Original on a reduced scale]




FIG.31.




FIG.32.




FIG.34.




FIG.33.





























FIG.35.

371,638 COMPLETE SPECIFICATION

SHEET 1



2 SHEETS
SHEET 2






FIG. 31.
FIG. 32.
FIG. 33.
FIG. 34.
FIG. 35.






FIG. 36.
FIG. 37.
FIG. 38.







FIG. 39.

FIG. 40.

FIG. 41.

FIG. 42.

FIG. 43.

FIG. 44.

FIG. 45.

FIG. 46.

FIG. 47.

FIG. 48.

FIG. 49.

FIG. 50.

FIG. 51.

FIG. 52.

FIG. 53.

FIG. 54.

FIG. 55.

